**Amendments to the Claims** 

This listing of claims will replace all prior versions, and listings, of claims in the

application:

**Listing of Claims:** 

1. (Original) A fluid dispensing system, comprising:

a pump body constructed and arranged to couple to a container, the pump body defining a

fluid inlet opening and a pump cavity;

an inlet valve constructed and arranged to allow fluid from the container to enter the pump

cavity through the fluid inlet opening;

a plunger slidably received in the pump cavity, the plunger defining a fluid passage through

which the fluid is dispensed; and

a shipping seal sealing the fluid passage to minimize leakage of the fluid before use.

2. (Original) The system of claim 1, further comprising an outlet valve disposed inside

the fluid passage to minimize fluid leakage between dispenses.

3. (Original) The system of claim 2, wherein the outlet valve includes a check valve.

4. (Original) The system of claim 2, wherein the outlet valve includes a valve member

and a spring engaging the valve member to bias the valve member into a normally closed position.

5. (Original) The system of claim 1, further comprising a shroud member covering the

inlet opening to draw fluid from the container.

6. (Original) The system of claim 1, further comprising a venting structure to equalize

air pressure inside the container.

Response to Office Action Serial No. 10/659,462 Group Art Unit 3754

CPS.le 378107

Attorney Docket No. 1104-767

Page 2 of 11

7. (Original) The system of claim 6, wherein the venting structure includes a vent opening defined in the pump body and a vent valve sealing the vent opening to allow air passage

into the container.

8. (Original) The system of claim 1, wherein the shipping seal is constructed and

arranged to seal the fluid passage when the plunger is fully retracted and to allow fluid flow into the

fluid passage when the plunger is extended.

9. (Original) The system of claim 1, wherein the shipping seal includes:

a seal member constructed and arranged to seal inside the fluid passage in the plunger;

a support flange engaging the pump body; and

a flow opening defined in the support flange to allow passage of fluid into the fluid passage.

10. (Original) The system of claim 9, wherein the seal member extends from opposite

sides of the support flange.

11. (Original) The system of claim 9, wherein the seal member includes a beveled edge.

12. (Currently amended) A fluid dispensing system, comprising:

a pump body constructed and arranged to couple to a container, the pump body defining a

fluid inlet opening inside the container and a pump cavity;

a plunger slidably received in the pump cavity to draw fluid from the container into the

pump cavity; and

a fluid pump constructed and arranged to dispense fluid from a container, the fluid pump

including a fluid intake end portion and a fluid dispensing end portion;

the fluid intake end portion being configured to extend within the container when the fluid

pump is coupled to the container to lower overall profile of the fluid dispensing system;

the fluid intake end portion having an inlet opening where the fluid from the container is

drawn into the fluid pump;

the fluid dispensing end portion being configured to extend outside the container when the

fluid pump is coupled to the container;

Response to Office Action Serial No. 10/659,462 Group Art Unit 3754

CPS.le 378107

Attorney Docket No. 1104-767

the fluid dispensing end portion having a dispensing opening where the fluid is dispensed from the fluid pump;

an intake shroud covering the inlet opening, the shroud including a flow channel with a channel opening configured to draw fluid from the container into the inlet opening; and

the flow channel of the shroud extending from the fluid intake end portion towards the fluid dispensing end portion, wherein the channel opening is located along the fluid pump between the inlet opening and the fluid dispensing end portion to increase evacuation efficiency of the fluid from the container.

- 13. (Original) The system of claim 12, further comprising the container.
- 14. (Currently amended) The system of claim 13, wherein:

the container is inverted and has a neck where the fluid pump is coupled to the container; the shroud, the plunger and the inlet opening extend inside the container; and the fluid pump is an inverted dispensing pump; and

the flow channel opening of the shroud opens at a position below the inlet opening in the neck of the container to draw the fluid in the neck that is located below the inlet opening.

15. (Currently amended) The system of claim 12, further comprising A fluid dispensing system, comprising:

a pump body constructed and arranged to couple to a container, the pump body defining a fluid inlet opening inside the container and a pump cavity;

a plunger slidably received in the pump cavity to draw fluid from the container into the pump cavity;

an intake shroud covering the inlet opening, the shroud including a flow channel to draw fluid from the container into the inlet opening; and

a shipping seal disposed inside the pump cavity to minimize fluid leakage during shipping.

16. (Currently amended) The system of claim 12, further comprising a venting structure defined in the <u>fluid</u> pump-body to equalize air pressure inside the container.

17. (Currently amended) The system of claim 12, further comprising:

a plunger slidably disposed in the fluid pump for pumping the fluid, wherein the plunger

defines a fluid passage that dispenses the fluid; and

an outlet valve disposed inside the fluid passage to minimize fluid leakage between

dispenses.

18. (Currently amended) A fluid dispensing system, comprising:

an inverted fluid dispensing pump comprising

\_\_\_\_a pump body defining a pump cavity[[;]],

a plunger slidably received in the pump cavity, the plunger defining a fluid passage

with a dispensing opening from which fluid is dispensed[[;]], wherein the dispensing

opening faces downwards when installed, and

an outlet valve disposed inside the fluid passage, wherein a height of the fluid in the

fluid passage between the outlet valve and the dispensing opening is reduced so that surface

tension of the fluid at the dispensing opening supports the fluid to minimize dripping of the

fluid from the dispensing opening.

19. (Original) The system of claim 18, further comprising a dispensing port coupled to

the plunger, the dispensing port defining a portion of the fluid passage and the dispensing opening,

wherein the outlet valve is disposed inside the fluid passage at an interface between the plunger and

the dispensing port.

20. (Original) The system of claim 19, wherein the outlet valve includes a spherical

shaped valve member and a spring biasing the valve member in a normally closed position.

21. (Original) The system of claim 18, wherein the outlet valve includes a check valve.

22. (Original) The system of claim 18, further comprising:

wherein the pump body defines one or more fluid intake openings; and

an intake shroud is disposed over the pump body to draw fluid into the intake openings.

Response to Office Action Serial No. 10/659,462 Group Art Unit 3754

CPS.le 378107

Attorney Docket No. 1104-767

23. (Original) The system of claim 22, further comprising an inlet valve disposed to seal the fluid intake openings.

24. (Currently amended) The system of claim 18, further comprising A fluid dispensing system, comprising:

a pump body defining a pump cavity;

a plunger slidably received in the pump cavity, the plunger defining a fluid passage with a dispensing opening from which fluid is dispensed;

an outlet valve disposed inside the fluid passage to minimize dripping of the fluid from the dispensing opening; and

a shipping seal constructed and arranged to seal the fluid passage to minimize fluid leakage during shipping.

- 25. (Currently amended) The system of claim 18, further comprising a vent opening defined in the vent pump body and a vent seal to seal the vent opening.
- 26. (New) The system of claim 12, wherein the fluid pump includes an inlet valve at the inlet opening, wherein the shroud allows fluid to be drawn to the inlet valve.

Response to Office Action Serial No. 10/659,462 Group Art Unit 3754 CPS.le 378107